

**REMARKS**

**INTRODUCTION:**

This preliminary amendment is being filed in order to improve the form of the above referenced application. In accordance with the foregoing, a substitute specification, replacement drawings and a new abstract are included in this Preliminary Amendment. Claims 1-12 have been amended and claims 13-19 have been added. No new matter is included in this amendment.

**CONCLUSION:**

There being no outstanding objections or rejections, it is submitted that the application is in condition for allowance. An early action to that effect is courteously solicited. Finally, if there are any formal matters remaining after this response, the Examiner is requested to telephone the undersigned to attend to these matters. If there are any additional fees associated with filing of this Amendment, please charge the same to our Deposit Account No. 503333.

Respectfully submitted,

STEIN, MCEWEN & BUI, LLP

Date: 5/26/06

By: 

Michael D. Stein  
Registration No. 37,240

1400 Eye St., NW  
Suite 300  
Washington, D.C. 20005  
Telephone: (202) 216-9505  
Facsimile: (202) 216-9510

Serial No. Not yet assigned

**IN THE SPECIFICATION:**

Please REPLACE the specification with the attached SUBSTITUTE SPECIFICATION. A clean version of the specification is also provided.

**AMENDMENTS TO THE DRAWINGS:**

Please include the attached replacement FIGS.1-5 in the application. Changes to the various figures relative to PCT application are as follows. All of the sheets have been revised to remove the PCT markings. In FIG. 4, the matrices have been identified by reference characters "H," "C," and "Z," to coordinate with the specification.

## Description

### TITLE OF THE INVENTION

ERROR CORRECTION METHOD AND APPARATUS FOR LOW DENSITY PARITY CHECK

### CROSS-REFERENCE TO RELATED APPLICATIONS

**[0001]** This application claims the benefit of PCT International Patent Application No. PCT/KR2004/003079, filed November 26, 2004, and Korean Patent Application No. 2003-85769, filed November 28, 2003 in the Korean Intellectual Property Office, the disclosures of which are incorporated herein by reference.

### BACKGROUND OF THE INVENTION

#### Technical Field1. Field of the Invention

**[0002]** Aspects of The~~the~~ present invention ~~relates~~relate to an error correction method and apparatus, and more particularly, to ~~an error correction~~a method of and an apparatus for determining whether an error exists in a decoded binary signal and correcting the error if the error exists in a decoding apparatus using a low density parity check (LDPC).

#### Background Art2. Description of the Related Art

**[0003]** A low density parity check (LDPC) encoding and decoding method refers to an error correction encoding and decoding technology used in a wireless communication field and an optical recording/reproducing field. An LDPC encoding includes a process of generating parity information using a parity check matrix. Here, most components of the parity check are 0, and very sparse components of the parity check matrix are 1.

**[0004]** The LDPC encoding ~~is~~may be divided into a regular LDPC encoding and an irregular LDPC encoding. In the regular LDPC encoding, the number of components equal to 1 included in a parity check matrix used for encoding and decoding is the same in every row and column. Otherwise, the LDPC encoding is irregular.

**[0005]** The LDPC encoding can be represented as shown in Equation 1.

~~{Equation 1}~~

$$H \times C_e = 0 \quad \dots(1)$$

where, H indicates a parity check matrix, 0 indicates a zero matrix, 'x' indicates an exclusive OR (XOR) operation and a modular 2 operation, and  $C_e$  indicates a code word vector, that is, a column matrix indicating a code word to be encoded. The code word includes an x-bit message word  $x_1, x_2, \dots, x_x$  and p-bit parity information  $p_1, p_2, \dots, p_p$ .

**[0006]** The parity information  $p_1, p_2, \dots, p_p$  is generated so that the message word  $x_1, x_2, \dots, x_x$  ~~satisfied~~ satisfies Equation 1. That is, since a binary value of the message word to be encoded among components of the parity check matrix H and matrix C is determined, parity information  $p_i$  ( $i = 1, 2, \dots, p$ ) can be determined using Equation 1.

**[0007]** The LDPC ~~encoding~~ decoding can be represented as shown in Equation 2.

{Equation-2}

$$H \times C_d = Z \quad \dots(2)$$

where, H indicates the same parity check matrix as that used for the encoding,  $C_d$  indicates a code word vector after passing a channel, and Z indicates a resultant matrix generated by performing a modular 2 operation on the ~~two H and  $C_d$  matrices~~. If an original code word is restored by successfully performing the decoding, that is, if  $C_e = C_d$ , the resultant matrix will be the zero matrix. That is, it is determined whether the decoding is successful by ~~determined~~ determining whether all components of the resultant matrix Z are 0.

**[0008]** More detailed descriptions of the LDPC encoding are described in ~~the article~~, "Good Error Correction Codes Based on Very Sparse Matrices" (D.J. MacKay, IEEE Trans. On Information Theory, vol. 45, no. 2, pp 399-431, 1999) and "Efficient Encoding of Low Density Parity Check Codes" (T. Richardson, R. Urbanke, IEEE Trans. On Information Theory, vol. 47, no. 2, pp 638-656, 2001).

**[0009]** However, according to the conventional LDPC-LDPC decoding method described above, since the resultant matrix Z cannot be equal to the zero matrix even if an error is generated in only one bit of the decoded word vector  $C_d$ , the decoding is determined as a failure. Therefore, the conventional LDPC decoding method is not an efficient decoding method.

~~Disclosure of Invention~~ SUMMARY OF THE INVENTION

~~Technical Solution~~

**[0010]** ~~The Aspects of the present invention provides~~ provide a low density parity check (LDPC) error correction method and apparatus for preventing a small number of errors from causing a total block to be determined as a decoding failure and correcting an error when it is determined that the error is in only one bit.

~~Advantageous Effects~~

**[0011]** According to ~~an~~ aspects of the LDPC decoding method and apparatus of embodiments of the present invention, the decoding apparatus using the LDPC can prevent a small number of errors from causing a total block to be determined as a decoding failure and correct an error when it is determined that a 1-bit error exists.

**[0012]** Additional aspects and/or advantages of the invention will be set forth in part in the description which follows and, in part, will be obvious from the description, or may be learned by practice of the invention.

~~Description of Drawings~~ BRIEF DESCRIPTION OF THE DRAWINGS

**[0013]** These and/or other aspects and advantages of the invention will become apparent and more readily appreciated from the following description of the embodiments, taken in conjunction with the accompanying drawings of which:

FIG. 1 is a flowchart of an LDPC error correction method according to ~~an aspect of an~~ embodiment of the present invention;

FIG. 2 is a block diagram of an error correction apparatus according to an embodiment of the present invention;

FIG. 3 illustrates correlations among components of matrices in a regular LDPC decoding;

FIG. 4 illustrates an example of correlations among components of matrices representing a principle of an error determination and correction method according to an embodiment of the

present invention; and

FIG. 5 is a flowchart of an error determination and correction method according to an embodiment of the present invention.

~~Best Mode~~ DETAILED DESCRIPTION OF THE EMBODIMENTS

**[0014]** According to an aspect of the present invention, ~~there is provided a~~ low density parity check (LDPC) error correction method ~~comprising~~comprises: generating a resultant matrix ( $m \times 1$ ) by performing an exclusive OR (XOR) operation and a modular 2 operation with respect to an LDPC matrix ( $m \times n$ ) and a code word vector ( $n \times 1$ ); determining whether a decoding of the code word vector succeeded based ~~on the basis of~~ the resultant matrix; and if it is determined that the decoding failed, detecting a code word bit, in which an error is generated, in the code word vector based ~~on the basis of~~ correlations of components of the LDPC matrix, the code word vector, and the resultant matrix.

**[0015]** According to another aspect of the present invention, ~~there is provided an~~ error determination method ~~comprising~~comprises: generating a resultant matrix ( $m \times 1$ ) by multiplying an LDPC matrix ( $m \times n$ ) by a code word vector ( $n \times 1$ ) and determining whether a decoding of the code word vector succeeded based ~~on the basis of~~ the resultant matrix; and if it is determined that the decoding failed, determining again whether the decoding succeeded based ~~on the basis of~~ a number of 1s included in the resultant matrix.

**[0016]** According to another aspect of the present invention, ~~there is provided a~~ low density parity check (LDPC) error correction apparatus ~~comprising~~comprises: a decoding success/failure checking unit generating a resultant matrix ( $m \times 1$ ) by performing an XOR operation and a modular 2 operation with respect to an LDPC matrix ( $m \times n$ ) and a code word vector ( $n \times 1$ ) and determining whether a decoding of the code word vector succeeded based ~~on the basis of~~ the resultant matrix; an error location detector searching ~~the a~~ a same column vector as the resultant matrix in the LDPC matrix and, if the same column vector exists, detecting an error location by detecting a column number of the same column vector.

~~Mode for Invention~~

**[0017]** Hereinafter, the present invention will now be described more fully with reference to the accompanying drawings, in which embodiments of the invention are shown. Reference will

now be made in detail to the present embodiments of the present invention, examples of which are illustrated in the accompanying drawings, wherein like reference numerals refer to the like elements throughout. The embodiments are described below in order to explain the present invention by referring to the figures.

**[0018]** FIG. 1 is a flowchart of an LDPC error correction method according to an embodiment of the present invention.

**[0019]** A decoding success/failure check of a decoded code word vector is performed in step operation 100. This step operation is performed by determining whether all components of a resultant matrix Z obtained by performing an XOR operation and a modular 2 operation of a parity check matrix H and decoded code word vector C are 0 in accordance with Equation 2, ~~as in the prior art.~~

**[0020]** If it is determined that the decoding ~~mailed~~ failed in step operation 100, that is, if even a single '1' is discovered in the resultant matrix Z, it is determined whether the generated error is a 1-bit error in step operation 110. A first condition of the 1-bit error is that ~~the a~~ a number of 1s generated in the resultant matrix Z is the same as ~~the a~~ a number of 1s included in a column of the parity check matrix H. That is, the first condition of 1-bit error is related to the number of errors. The reason is because a change of a code word bit influences generation of the resultant matrix Z as much as the number of 1s included in a specific column of the parity check matrix H. As a result, if the number of 1s included in the resultant matrix Z is not the same as the number of 1s included in a column of the parity check matrix H, it is determined that the error is not the 1-bit error.

**[0021]** If it is determined that the error is not the 1-bit error in step operation 110, a decoder (not shown) determines that the decoding failed and finished the decoding process at the moment. However, if it is determined that the error is the 1-bit error in step operation 110, it is determined whether the decoded code word vector C satisfies a second condition to be the 1-bit error in step operation 120. The second condition to be the 1-bit error is that the same column vector as the resultant matrix Z must exist in the parity check matrix H. That is, the second condition to be the 1-bit error is related to an error location. The second condition will be described in detail with reference to FIGS. 3 and 4.



**[0022]** If the two conditions to be the 1-bit error are satisfied in ~~steps-operations~~ 110 and 120, a 1-bit error correction is performed in ~~step-operation~~ 130. The 1-bit error correction is performed by changing binary values of code word bits corresponding to a column number of the column vector detected in ~~step-operation~~ 120 in the code word vector.

**[0023]** FIG. 2 is a block diagram of an error correction apparatus according to an embodiment of the present invention.

**[0024]** Referring to FIG. 2, the error correction apparatus includes a decoding success/failure checking unit 210, an error count detector 220, an error location detector 230, and a binary value changing unit 240. The decoding success/failure checking unit 210 determines whether a decoding succeeded or failed by generating a resultant matrix  $Z$  (221) from a code word vector  $C$  (211), which is decoded binary signal, and a parity check matrix  $H$ , and determining whether all components of the resultant matrix  $Z$  (221) are 0.

**[0025]** If it is determined that the decoding failed, the error count detector 220 receives the resultant matrix  $Z$  (221), detects ~~the a~~ number of 1s included in the resultant matrix  $Z$  (221), and determines whether the number of detected 1s is the same as a column weight of the parity check matrix  $H$ . If ~~they~~ the number of detected 1s and the column weight of the parity check matrix  $H$  are the same, the error count detector 220 generates a first condition satisfaction signal 231 and transmits the signal 231 to the error location detector 230. When the error location detector 230 receives the first condition satisfaction signal 231 from the error count detector 220, the error location detector 230 searches whether the same column vector as the resultant matrix  $Z$  (221) exists in the parity check matrix  $H$ . If the same column vector exists, the error location detector 230 transmits a second condition satisfaction signal 241 and a column number  $k$  of the detected column vector to the binary value changing unit 240.

**[0026]** When the binary value changing unit 240 receives the second condition satisfaction signal 241 from the error location detector 230, the binary value changing unit 240 corrects the error by changing a binary value of a code word bit, which has the same number as the column number  $k$  of the column vector received from the error location detector 230, in the code word vector  $C$  (211).

**[0027]** FIG. 3 illustrates correlations among components of matrices in a regular LDPC decoding.

**[0028]** An LDPC matrix H is an  $m \times n$  matrix having components  $h_{11}$  through  $h_{mn}$ . In a regular LDPC encoding, ~~the a same~~ number of 1s is included in each row  $R_1, R_2, R_3, \dots, R_n$  ~~is all the same~~, and ~~also, the a same~~ number of 1s included in each column  $C_1, C_2, C_3, \dots, C_n$  ~~is all the same~~. Here ~~the~~ The number of 1s in each row  $R_1, R_2, R_3, \dots, R_n$  is called a row weight, and the number of 1s included in each column  $C_1, C_2, C_3, \dots, C_n$  is called a column weight. In a typical regular LDPC encoding, the row weight is 3, and the column weight is usually 9, which is ~~a triple number of~~ three times the row weight.

**[0029]** In a regular LDPC decoding, each row  $R_1, R_2, R_3, \dots, R_n$  is different from each other row, and each column  $C_1, C_2, C_3, \dots, C_n$  is also different from each other column. That is,  $R_1, R_2, R_3, \dots, R_n$ , are respectively different and also,  $C_1, C_2, C_3, \dots, C_n$  are respectively different. This feature is used for an error correction that ~~will be described later~~ is described below.

**[0030]** A decoded word vector C includes code word bits  $x_1, x_2, x_3, \dots, x_n$  including information bit and parity bit. The resultant matrix Z is generated by performing a modular operation of the LDPC matrix H and decoded word vector C.

**[0031]** Correlations among components of the matrices are represented as shown in Equations 3.

{Equation 3}

$$\left. \begin{array}{l} \text{mod } 2[h_{11}x_1 + h_{12}x_2 + \dots + h_{1n}x_n] = z_1 \\ \text{mod } 2[h_{21}x_1 + h_{22}x_2 + \dots + h_{2n}x_n] = z_2 \\ \dots \\ \text{mod } 2[h_{m1}x_1 + h_{m2}x_2 + \dots + h_{mn}x_n] = z_m \end{array} \right\} \dots (3)$$

Here, if any one of  $z_1, z_2, z_3, \dots, z_n$  is 1, it is determined that the decoding failed.

**[0032]** FIG. 4 illustrates correlations among components of matrices representing a principle of an error determination and correction method according to an embodiment of the present invention.

**[0033]** Referring to FIG. 4, a column weight (CW) is 3, and a parity check matrix H is a  $10 \times 20$  matrix. Code word bits  $x_1, x_2, x_3, \dots, x_{20}$  indicates decoded code word bits. A resultant matrix Z is a column vector having 10 components.

**[0034]** In ~~this~~ the example shown in FIG. 4 ~~embodiment~~, third, seventh, and tenth components of the resultant matrix Z are 1. This resultant matrix Z indicates that the LDPC decoding failed. Now, it is ~~examined-determined~~ that each ~~which~~ component of the resultant matrix Z is generated from ~~what~~ which components of the parity check matrix H and decoded code word vector C and ~~that the~~ which components give ~~what~~ which kind of influences to the error. The above ~~things~~ determinations can be ~~known-made~~ by examining Equation 3.

**[0035]** A first '1' (411) of the resultant matrix Z is generated by performing the modular operation of a third row R3 of the parity check matrix H and the code word column vector. A second '1' (412) of the resultant matrix Z is generated by performing the modular operation of a seventh row R7 of the parity check matrix H and the code word column vector. Likewise, a third '1' (413) of the resultant matrix Z is generated by performing the modular operation of a tenth row R10 of the parity check matrix H and the code word column vector. If the decoded code word vector C ~~was-were to be~~ the same as a code word vector C, ~~any-no~~ '1' would ~~not~~ appear in the resultant matrix Z. However, since at least one '1' ~~appeared~~ appears in the resultant matrix Z, it can be predicted that binary values of one or more (unknown yet) bits among code word bits of the decoded code word vector C were changed. In the embodiment of the present invention, when only one code word bit is changed, that is, when a 1-bit error is generated, a location where the error is generated is predicted.

**[0036]** ~~In the example shown in FIG. 4,~~ it is assumed that an error is generated in one bit of the decoded code word vector C and a location where the error is generated is a tenth code word bit  $x_{10}$  of the decoded code word vector C. In Equation 3, when the resultant matrix Z is generated, the code word bit  $x_{10}$  is modular 2 operated with each bit of a tenth column  $C_{10}$  of the parity check matrix H. However, the code word bit  $x_{10}$  is not modular 2 operated with all bits of the tenth column  $C_{10}$  since there are components having a value 0. That is, the code word bit  $x_{10}$  is modular 2 operated in only locations where '1' exists among components of the tenth column  $C_{10}$ , and as a result only the locations ~~influences~~ influence the generation of components of the resultant matrix Z. In ~~this embodiment~~ the example shown in FIG. 4, since

the locations where a component of the tenth column  $C_{10}$  is 1 are the third, seventh, and tenth bits, 1s appear in the third, seventh, and tenth locations of the resultant matrix Z.

**[0037]** As a result, if only a 1-bit error is generated, it can be known that column numbers of the parity check matrix H having '1' in the same locations as those where '1' appears in the resultant matrix Z are the same as numbers of code word bits where errors are generated in the decoded code word vector C. However, this proposition is ~~effected under an~~ assumption assumes that the parity check matrix H is a regular LDPC matrix and an error is generated in only one bit of the code word. If the error is not the 1-bit error, since a plurality of code words influence generation of components of the resultant matrix, ~~and since a row of the parity check matrix and the generation of components of the resultant matrix,~~ and since a row of the parity check matrix and the generation of components of the resultant matrix do not have a one-to-one relationship, ~~nobody knows which the~~ code word bits which influence the generation of the resultant matrix are unknown.

**[0038]** As described above, a bit where an error is generated in the code word can be ~~known~~ determined by examining the resultant matrix. ~~This is performed as follows.~~

**[0039]** First, bit numbers whose values are 1 in ~~a the~~ the resultant matrix are detected. In the ~~embodiment example shown in~~ of FIG. 4, the bit numbers whose components have 1 in the resultant matrix are 3, 7, and 10, references (411), (412) and (413), respectively.

**[0040]** Second, the parity check matrix H is searched for a column  $C_k$  having 1 bits in the a ~~same locations location~~ as those of 1 bits detected in the first procedure in a parity ~~check resultant matrix is searched.~~ In a regular LDPC, since every column of the parity check matrix is different from each other, the searched column  $C_k$  having 1 bits in the same location as the resultant matrix is unique. In the ~~embodiment of~~ example shown in FIG. 4, the column  $C_k$  is  $C_{10}$ , and the corresponding 1 bits are identified by references (401), (402) and (403), respectively.

**[0041]** Third, a code word bit having ~~the a~~ the same number as that the number of the column  $C_k$  having 1 bits which match the 1 bits of the resultant matrix obtained in the second procedure is determined to be the code word bit where the error is generated. In the ~~embodiment example~~ shown in of FIG. 4, the code word bit having the error is determined to be  $x_{10}$ .

[0042] As described above, it is assumed that a 1-bit error is generated and every column of a parity check matrix has the same column weight. Therefore, if the number of bits having 1 in the resultant matrix in the first procedure is not the same as the column weight (for example, the number of bits having 1 in the resultant matrix is 4), ~~the method according to the present invention cannot be adapted~~ an error bit is not determined.

[0043] An LDPC matrix used for optical disc systems usually uses cases where  $m = 1000$  through  $10000$  and  $n = 3000$  through  $30000$ . If it is considered that a general bit error rate (BER) of a DVD is  $10^{-12}$ , a proportion of generating errors in two bits or more with respect to one code word vector (3000 through 30000 bits) is way very low. Therefore, in general optical disc systems, a very large error correction effect can be achieved with only a 1-bit error correction.

[0044] FIG. 5 is a flowchart of ~~an~~ a method of error determination and correction method according to an embodiment of the present invention.

[0045] Steps/Operations 510 and 520 indicate ~~a procedure of detecting~~ detect whether an error exists in an encoded code word vector C. The decoding success/failure checking unit 210 generates a resultant matrix Z by multiplying a parity check matrix H used in an encoding process and a decoded code word vector C and performing a modular 2 operating operation on respective components of the two matrices in step operation 510. The decoding success/failure checking unit 210 checks whether all components of the resultant matrix Z are 0 in step operation 520. Since the modular 2 operation was performed, if ~~any~~ an error was not generated in the decoded code word vector C, all components of the resultant matrix Z should be 0. However, if at least one '1' exists in the components of the resultant matrix Z due to error generation, ~~this process~~ the method proceeds to step operation 530.

[0046] Steps/Operations 530 and 540 indicate a first procedure ~~for~~ determining whether the error generated in the decoded code word vector C is a correctable error according to the embodiment of the present invention, that is, whether the error is a 1-bit error. If it is determined that at least one '1' is included in the components of the resultant matrix Z in step operation 520, the error count detector 220 detects the number of 1s included in the resultant matrix Z in step operation 530 and determines whether the number of 1s is included in the decoded code word vector C is the same as a column weight (CW) of the parity check matrix in step operation 540.

if the number of 1s included in the decoded code word vector C is different from the CW of the parity check matrix H in step-operation 540, since the error is not the 1-bit error, ~~it is impossible to correct the error~~ cannot be corrected according to the embodiment of the present invention. Accordingly, it is determined that the decoding failed. If the number of 1s included in the decoded code word vector C is the same as the CW of the parity check matrix H in step operation 540, ~~this process~~ the method proceeds to step-operation 550.

**[0047]** Steps-Operations 550 through 570 indicate a second procedure for determining whether the error generated in the decoded code word vector C is a correctable error according to the embodiment of the present invention, that is, whether the error is a 1-bit error. If it is determined that the number of 1s included in the decoded code word vector C is the CW of the parity check matrix H in step-operation 540, the error location detector 230 compares each column matrix  $C_1, C_2, C_3, \dots, C_n$  included in the parity check matrix H to the resultant matrix Z in step-operation 550 and determines whether a column matrix  $C_k$  is the same as the resultant matrix Z exists in step-operation 560. If the same it is determined that a column matrix  $C_k$  which is the same as the resultant matrix Z does not exist in step-operation 560, since '1' is generated due to a third cause not the 1-bit error, it is impossible to correct the error cannot be corrected according to the embodiment of the present invention, since the error is not the 1 bit error. Accordingly it is determined that the decoding failed. If the column matrix  $C_k$  which is the same as the resultant matrix Z exists in step-operation 560, a column number k of the column matrix  $C_k$  is extracted in step-operation 570.

**[0048]** The binary value changing unit 240 generates a corrected code word vector  $C-C'$  by changing a binary value of the  $k^{\text{th}}$  code word bit of the decoded code word vector C, that is, changing 0 to 1 or 1 to 0, in step-operation 580. Since every codeword bit has only a value of 0 or 1, if the error is generated on a value 0, 1 is a value before the error is generated. Accordingly, the binary value changing allows the error to be corrected.

**[0049]** In steps-operations 590 and 600, the decoding success/failure checking unit 210 confirms whether the correction is achieved by checking ~~on the corrected code word vector  $CC'$  whether the decoding succeeded using the a same procedure as steps-operations 510 and 520.~~

**[0050]** ~~While this invention has been particularly shown and described with reference to preferred embodiments thereof, it will be understood by those skilled in the art that various~~

~~changes in form and details may be made therein without departing from the spirit and scope of the invention as defined by the appended claims. The preferred embodiments should be considered in descriptive sense only and not for purposes of limitation. Therefore, the scope of the invention is defined not by the detailed description of the invention but by the appended claims, and all differences within the scope will be construed as being included in the present invention. Although a few embodiments of the present invention have been shown and described, it would be appreciated by those skilled in the art that changes may be made in this embodiment without departing from the principles and spirit of the invention, the scope of which is defined in the claims and their equivalents.~~